

YEALINK T57W

Wireless-enabled
Gigabit IP Phone



Yealink

Gigabit IP phone supports up to 16 lines, HD voice, color LCD touch screen and built-in Wi-Fi.

Designed for busy executives and professionals, the Yealink T57W is an easy-to-use business phone perfect for any work location. With a 7-inch adjustable color touch screen LCD display, the T57W can be used anywhere utilizing either gigabit LAN connectivity, or its Bluetooth 4.2 and dual band 2.4G/5G Wi-Fi connections.

- 7" 800 x 480 Capacitive Adjustable Touch Screen
- Built-in Bluetooth 2.4 and Dual Band 2.4G/5G Wi-Fi
- Gigabit Ethernet
- PoE Support



T54W IP PHONE PRODUCT SPECIFICATIONS

Audio Features:

- HD voice: HD handset, HD speaker
- Hearing aid compatible (HAC) handset
- Acoustic Shield
- Audio codec: Opus, G.722, PCMA, PCMU, G.729A/B
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- CNG, AEC, PLC, AJB, AGC

Phone Features:

- 16 VoIP accounts
- Call hold
- One-touch speed dial
- Hotline
- Call forward, call waiting, call transfer
- Mute, DND
- Group listening, SMS
- Emergency call
- Redial, call return,
- Auto answer
- 3-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan, XML Browser, Action URL/URI
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- Built-in dual band Wi-Fi:
 - Network standard: IEEE802.11a/b/g/n/ac
 - Transmission rate: up to 433Mbps (dynamic)
 - Frequency range: 2.4GHz/5.0GHz
- Built-in Bluetooth for:
 - Bluetooth headset
 - Mobile contacts synchronization
 - Bluetooth call
- USB port (2.0 compliant) for:
 - Wired/wireless USB headset
 - USB call recording through USB flash drive
 - Color-screen expansion modules EXP50 (up to 3)

- Content Sharing (via Yealink VCD)
- Enhanced DSS key

Directory:

- Local phonebook up to 1000 entries
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

Corded-Cordless Phone (via DECT Dongle DD10K):

- Up to 4 DECT cordless handsets
- Up to 4 concurrent calls
- Support Yealink W52H/W53H/W56H/DD Phone
- Slave Handset for Master Deskset

IP-PBX Features:

- Busy Lamp Field (BLF), Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Flexible seating, Executive and Assistant
- Call park, call pickup
- Centralized call recording, call recording

Display and Indicator:

- 7" 800 x 480 capacitive adjustable touch screen
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Wallpaper
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name, number and photo
- Screensaver
- Power saving

Feature Keys:

- 29 one-touch DSS keys
- 7 feature keys: hold, transfer, message, headset, mute, redial, speakerphone

T54W IP PHONE PRODUCT SPECIFICATIONS

- Volume control keys
- Illuminated mute/headset/hands-free speakerphone key

Interface:

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af)
- 1 x USB port (2.0 compliant)
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

Management:

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Broadsoft device management
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

Network and Security:

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP/PPPoE
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS1.2)
- HTTPS certificate manager

- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X
- IPv6, LLDP/CDP/DHCP VLAN, ICE

Other Physical Features:

- Color: Classic Grey
- Wall mountable (optional)
- External Yealink AC adapter (optional): AC 100~240V input and DC 5V/2A output
- USB output currency: 5V 500mA
- Power consumption (PSU): 3.2W-6.3W
- Power consumption (PoE): 4.0W-7.8W
- Dimension (W*D*H*T): 259.4mm*220mm*211mm*44.5mm
- Operating humidity: 10~95%
- Operating temperature: 0~40°C (+32~104°F)

Package Features:

- Package content:
 - Yealink SIP-T57W IP phone
 - Handset with handset cord
 - Ethernet Cable
 - Stand
 - Quick Start Guide
 - Power Adapter (Optional)
- Qty/CTN: 5 PCS
- N.W/CTN: 8.86 kg
- G.W/CTN: 9.79 kg
- Giftbox size: 324 mm*293 mm*128 mm
- Carton measurements: 680 mm* 303 mm*342 mm



J.D. Power 2020 Certified Assisted Technical Program, developed in conjunction with TSIA. Based on successful completion of an audit and exceeding a customer satisfaction benchmark for assisted support operations. For more information, visit www.jdpower.com or www.tsia.com. Intermedia Unite, SecuriSync, VoIP Scout, AnyMeeting and HostPilot are either trademarks or registered trademarks of Intermedia.net, Inc. in the United States and/or other countries.

Questions? Contact Intermedia today.
800.379.7729 | sales@intermedia.com
intermedia.com

